



- 设计压力4.1MPa (600PSI)  
Design Pressure 4.1MPa (600PSI)
- 设计温度66°C (150° F)  
Design Temperature 66°C (150° F)
- 最低允许温度-10°C (14° F)  
Min Temperature -10°C (14° F)
- 工作介质为PH3-10的水  
Media: Water PH3-10
- 净水口压力为0.88MPa (125PSI)  
0.88MPa (125PSI)
- 项目3数量由客户选择决定; 项目5仅在浓水端  
The number of items 3 is determined by the customer's choice; Item 5. At the end of concentrated water only
- 图纸仅供参考, 具体以实物为准  
Drawings are for reference only, in kind
- 请按照说明书正确使用  
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	P (mm)	重量 WEIGHT (kg)
1	698 (27.5)	1478 (58.2)	1147 (45.2)	45 (99)
2	1714 (67.5)	2494 (98.2)	2163 (85.2)	58 (127.6)
3	2730 (107.5)	3510 (138.2)	3179 (125.2)	71 (156.2)
4	3746 (147.5)	4526 (178.2)	4195 (165.2)	84 (184.8)
5	4762 (187.5)	5542 (218.2)	5211 (205.2)	97 (213.4)
6	5778 (227.5)	6558 (258.2)	6227 (245.2)	110 (242)
7	6794 (267.5)	7574 (298.2)	7243 (285.2)	123 (270.6)

17	紧固螺母 FASTENING NUT	2	工程塑料 Engineering Plastic
15/16	挡块+挡块螺丝 LINK STOPPER+BAFFLE FIXING BOLTS	6	SUS304
14	嵌入钢圈 EMBEDDED RING	2	SUS304
12/13	钢带 STRAP+螺丝 SCREWHEAD (螺栓尺寸: M8*90)	2-3	A-666, 304+A216
11	鞍座 SADDLE (3芯以上均为3个)	2-3	TPU (S60D)
10	密封板 SEALBOARD	2	ABS
09	适配器 ADAPTOR	2	ABS
08	适配器大/小O型圈 ADAPTOR LARGE/SMALL O GLUE	4+4	EPDM 512
07	密封板O型圈 SEALING PLATE O-RING	2	EPDM 512
06	承载板 BEARING PLATE	2	SB-209, 6061-T651
05	止推环 THRUST CONE	1	工程塑料 Engineering Plastic
04	侧口两圈 SIDE DORT	2	SUS304
03	侧口 SIDE PORT	2	SUS316L
02	侧口密封圈 SIDE PORT SEAL RING	4	EPDM 512
01	壳体 SHELL	1	FIBER GLASS +EPOXY

原浓水口规格	D	H
1.5" (DN40)	256	155
2" (DN50)	260	158
2.5" (DN65)	279	164

SIGNATURE		
NAME	DATE	
设计 陈勇	2019.4.19	
审核		
审批		

**Winder** 河北成达华膜科技有限公司  
Hebei Chengda HuaMo Technology Co., Ltd

型号 TYPE W80S600	单位 UNIT: MM
--------------------	----------------

仅供参考, 零部件以图纸为准, 变更不另行通知

THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY