



- 1、设计压力8.3MPa(1200PSI)  
Design Pressure 8.3MPa(1200PSI)
- 2、设计温度66℃ (150° F)  
Design Temperature 66℃ (150° F)
- 3、最低允许温度-10℃ (14° F)  
Min Temperature -10℃ (14° F)
- 4、工作介质为PH3-10的水  
Media:Water PH3-10
- 5、净水口压力为0.88MPa (125PSI)  
Water mouth pressure 0.88 MPa(125 PSI)
- 6、项目5仅在浓水端  
Item 5. At the end of concentrated water only
- 7、图纸仅供参考，具体以实物为准  
Drawings are for reference only, in kind
- 8、请按照说明书正确使用  
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	重量 WEIGHT (kg)
1	790 (31.1)	1550 (61)	
2	1806 (71.1)	2566 (101)	
3	2822 (111.1)	3582 (141)	
4	3838 (151.1)	4598 (181)	
5	4854 (191.1)	5614 (221)	
6	5870 (231.1)	6630 (261)	
7	6886 (271.1)	7646 (301)	

18	紧固螺母 FASTENING NUT	2	工程塑料 Engineering Plastic
17	螺栓 BOLT	6	SUS304
16	定位环 POSITIONING RING	2	工程塑料 Engineering Plastic
15	挡块 LINK STOPPER+BAFFLE FIXING BOLTS	6	316
14	嵌入钢圈 EMBEDDED RING	2	316
12/13	钢带 STRAP+螺丝 SCREWHEAD (螺栓尺寸: M8*90)	2-3	A-666, 304+A216
11	鞍座 SADDLE (3芯以上均为3个)	2-3	TPU(S60D)
10	密封板 SEALBOARD	2	ABS
09	适配器 ADAPTOR	2	ABS
08	适配器大/小型圈 ADAPTOR LARGE/SMALL O GLUE	4+4	EPDM 512+硅胶
07	密封板 O型圈 SEALING PLATE O-RING	2	EPDM 512
06	承载板 BEARING PLATE	2	SB-209, 6061-T651
05	止推环 THRUST CONE	1	工程塑料 Engineering Plastic
04	两圈挡环 TWO RINGS	4	SUS304
03	密封胶圈 SEALED RUBBER RINGS	4	EPDM 512
02	进、出水口 ACCESS TO WATER	2	SUS316
01	壳体 SHELL	1	FIBER GLASS +EPOXY
	名称	数量	材料

SIGNATURE		
设计	陈勇	2019.1.31
审核		
审批		
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY		

**Winder® 河北成达华膜科技有限公司**  
Hebei Chengda Hualuo Technology Co., Ltd

型号 TYPE	单位 UNIT:
W80E1200	MM
仅供参考，零部件以图纸为准，变更不另行通知	